

STAR - DELTA STARTER



Ordering Information :

Model No.	Descriptions	Output type
SD 1209	Double Display, Suitable to 1 HP to 7.5 HP, Star Delta	Star Delta (12, 12, 09 AMP Contractor)
SD 1812	Double Display, Suitable to 1 HP to 10.0 HP, Star Delta	Star Delta (18, 18, 12 AMP Contractor)
SD 2518	Double Display, Suitable to 1 HP to 15.0 HP, Star Delta	Star Delta (25, 25, 18 AMP Contractor)
SD 3225	Double Display, Suitable to 1 HP to 20.0 HP, Star Delta	Star Delta (32, 32, 25 AMP Contractor)
SD 5040	Double Display, Suitable to 1 HP to 30.0 HP, Star Delta	Star Delta (50, 50, 40 AMP Contractor)
SD 6550	Double Display, Suitable to 1 HP to 40.0 HP, Star Delta	Star Delta (65, 65, 50 AMP Contractor)
SD 8065	Double Display, Suitable to 1 HP to 60.0 HP, Star Delta	Star Delta (80, 80, 65 AMP Contractor)
SD 9580	Double Display, Suitable to 1 HP to 70.0 HP, Star Delta	Star Delta (95, 95, 80 AMP Contractor)

Input type	R, Y, B, Three Phase
Supply	450 VAC, 50 Hz (±10%)

- » Exclusively Designed to Operate Three Phase Star Delta Submersible Motor and Pump at Domestic Industrial and Agricultural
- » Built in Auto Switch
- » Micro Controller Baser Advance Phase Lose, Phase Sequence Over Voltage, Under Voltage, Over Load, Dry Run and Current Unbalance Protection
- » Delay OFF, Cyclic Timer
- » Fault Indication ON Display
- » It Protects Against Voltage Fluctuation Which Again Can Cause Damage to the Motor Or Pump
- » Auto and Manual Mode